

REWIND

REWIND 900 FLAT CONTRACT



Produced using
zero latex



Zero water



Just a fraction
of energy use



Significantly lower
carbon emissions

Nature is a series of intricate cycles. Every ending starts a new beginning... It's time to rethink our connection with nature and close the loop! Introducing Rewind, the ultimate recyclable flooring solution. Rewind is stylish, durable and sustainable.

Produced using **zero latex**, **zero water** and with just **a fraction of energy use**. Rewind delivers significantly **lower carbon emissions** compared to traditional flooring.

And just like in nature, not a single fiber goes to waste. Rewind is made from only one material, so every carpet can be easily recycled and given a new life.

Rethink. Reinvent. **Rewind.**



A division of
Beaulieu International Group
BFS Europe NV
Groenedreef 15A, 9770 Kruisem
www.beaulieu-needlefelt.com

DNF.RO.MAR.15a/3/01-04-2024
Update: 04-2024



Technical specifications

Manufacturing process	DIN 61151	Needle felt
Pile composition	-	100% PP
Surface structure	-	Flat
User class	-	33
Backing	ISO 2424	None - latex free
Pile weight	ISO 8453	900 g/m²
Total weight	ISO 8453	900 g/m²
Pile height	ISO 1765	5 mm
Total height	ISO 1765	5 mm
Roll length	-	30 m
Impact noise reduction	-	20 dB
Permanent anti-static	ISO 6356	≤ 2kV
Thermal resistance	ISO 8302	0,0832 m² K/W
Resistance to rubbing	ISO 105-X12	≥ 5
Prodis GUT Certificate	-	943358A6
Fire classification	EN 13501-1	Bfl-s1



Colours may slightly vary from batch to batch.
Characteristics in line with EN 1307 standards.
We reserve the right to alter technical specifications.
Protection foil is not suitable in humid conditions.
© Beaulieu International Group

REWIND 900 FLAT

Colour	2 m	4 m
1098	✓	✓
2077	✓	✓
2158	✓	✓
2190	✓	✓
2225	✓	✓
2241	✓	✓
2266	✓	✓
3088	✓	✓

Colour	2 m	4 m
5100	✓	✓
5131	✓	✓
5151	✓	✓
6099	✓	✓
6125	✓	✓
7001	✓	✓
7055	✓	✓
7104	✓	✓

